

# Water-Based **ML745** AntiCorrosive**Topside**



## FEATURES

**ENDRUST® “ML745” Water-Based TOPSIDE** is a unique blend of selected waxes, resins and corrosion control agents formulated to comply with AS2662 Corrosion Inhibition (Rust Proofing) Motor Vehicles Part 1.

**ENDRUST® “ML745” Water-Based TOPSIDE** is fortified with corrosion preventatives. It is rheology controlled to give excellent atomization with a fogging attachment, particularly with low-pressure systems, and has excellent seam penetration with negligible sag and run.

## RECOMMENDED USES

**ENDRUST® “ML745” Water Based TOPSIDE** is designed to inhibit the formation of rust in internal box sections, door cavities, sills, and pillars of motor vehicles and dries to a soft waxy protective coating. It is designed to be applied directly to metal or painted surfaces, where water displacing, water repellent, inner body corrosion preventative is required.

## SPECIFICATION DATA

<b>Colour:</b>	Light brown opaque fluid	<b>WFT:</b>	125 micron
<b>Viscosity:</b>	550-650cps @ 25°C	<b>DFT:</b>	75-100 micron
<b>Volume Solids:</b>	~25%	<b>Number of Coats:</b>	1 coat
<b>Packaging:</b>	20L, 200L	<b>Touch Dry:</b>	24 hours
<b>Application:</b>	Direct or Spray Mist	<b>Full Cure:::</b>	10 Days
<b>Cleanup (Wet):</b>	Water	<b>Storage:</b>	Cool, Dry conditions
<b>Cleanup (Cured):</b>	White Spirit or Thinners		

## PERFORMANCE

<b>Temperature Resistance</b>	Good
<b>Weatherability</b>	Excellent
<b>Corrosion Resistance</b>	Excellent

## DIRECTIONS FOR USE

**ENDRUST® ML745 Water Based TOPSIDE** can be applied by light airless spray equipment with special nozzles or using an air-mix pistol spray gun with an air pressure of 3-6 bar / 45 to 90 psi. If necessary, the product can also be dipped, rolled, or brushed. Depending on the application the product can be thinned with water. Over-spray, or equipment contaminated with over-spray, must be cleaned while still wet with water or a solvent.

Water-Based  
**ML745**  
AntiCorrosive**Topside**



PRECAUTIONS

See the Safety Data Sheet (SDS) for health and safety information prior to use.

CONTACT

ENDRUST AUSTRALIA  
(ABN: 62 651 348 659)

23b Fairbrother St, Belmont Western Australia 6104  
Telephone (+61) 8 9325 1399 Fax (+61) 8 9325 2431  
[info@endrust.com.au](mailto:info@endrust.com.au)  
[www.endrust.com.au](http://www.endrust.com.au)

***ENDRUST - The Name You Can Trust !***

**Disclaimer**

This is not a specification, and all the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use and whether there is any infringement of patents is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance, or injury. For application in special conditions, consult the manufacturer for detailed recommendations.