

1. Product and Company Identification

Company Name: ENDRUST AUSTRALIA

23b Fairbrother Street, Belmont. WA 6104 info@endrust.com.au

Contact: Endrust (08) 9325 1399 Poisons Information Centre 13 11 26

Product Name:	ENDRUST® CHASSIS SHIELD	
Other Names:	Clear Rust & Corrosion Preventative	
Product Code:	1400	
Intended Use:	Lubricant and corrosion preventative	
Chemical Nature:	Mixture	

2. Hazards Identification

Hazard Classification:	Hazardous Chemical according to classification by Safe Work Australia Non-Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.			
GHS Classification:	Aspiration Hazard C	ategory 1.		
GHS Signal Word:	DANGER	DANGER		
Hazard Statement:	H304 May be fatal i	H304 May be fatal if swallowed and enters airways.		
Precautionary Statements:	General: Response:	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. P301+P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician P331 Do NOT induce vomiting.		
	Storage: Disposal:	P405 Store locked up. P501 Dispose of contents/container in accordance with local regulations.		

3. Composition / Information on Ingredients

Ingredients Name	Cas Number	Proportion (%)
Distillates (petroleum), hydrotreated	64742-46-7	40 - 70
Middle; Gas oil – unspecified Linseed Oil	8001-26-1	5 – 30
Xylene	1330-20-7	1 - 25
Long Oil Alkyd Resin	000000-30-3	1 - 40
Ingredients determined to be non-hazardous		

CHASSIS SHIELD SDS Issued: October 10, 2025 Page 1 of 5



4. First aid Measures				
In case of Eye Contact:	If in eyes, hold eyes open, flood with water for at least 15 minutes. If symptoms persist, transport to nearest medical facility for additional treatment.			
In case of Skin Contact:		If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available.		
If Inhaled:	Keep victim calm and remove to fresh air if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment. Remove contaminated Clothing.			
If Ingested:	If swallowed, do NOT induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.			
Symptoms caused by Exposure:	Inhalation: Breathing of high vapours concentrations may have a narcotic effect on the central nervous system Skin: May include redness and itching. Eyes: May include burning and temporary redness. Ingestion: May cause mild gastrointestinal irritation, nausea, vomiting and diarrhea.			
Medical attention and special Treatment:	Treat symptomatic	ally.		

5. Fire Fighting Measures

Suitable Extinguishing Media:	Foam, water spray or fog, dry chemical powder, or carbon dioxide. Do not use water in a jet.		
Specific Hazards arising from the Chemical:	Will float and can be reignited on surface of water. Vapour is heavier than air, can spread along ground and distant ignition is possible.		
Special protective equipment for fire fighters:	Wear full protective clothing and self-contained breathing apparatus. Hazchem code.		

6. Accidental Release Measures

Personal Precautions: Avoid contact with spilled or released material. Shut off leaks, if possible, without risks. Isolate hazard area and deny entry to unnecessary or unprotected personne sources of ignition in the surrounding area. Take precautionary measures against discharge. Ensure electrical continuity by bonding and earthing all equipment.			
Environmental Precautions:	Use appropriate containment to avoid environmental contamination. Prevent from spreading and entering waterway using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location, for example by using fog sprays. Ventilate contaminated area thoroughly.		
Methods of cleanup:	For small spills (<1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely. For larger spills (>1drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Do not flush residues with water. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.		

7. Handling and Storage

Precautions for safe handling:	Combustible product. Avoid breathing vapours. Handle and open containers with care in a well-ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Avoid contact with skin, eyes, and clothing. Wash thoroughly after handling. Do not eat, drink, or smoke in contaminated areas. Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment.	
Conditions for safe storage:	Store in a well ventilated area, away from sunlight, ignition sources and other sources of heat. Do not store near strong oxidants.	

CHASSIS SHIELD SDS Issued: October 10, 2025 Page 2 of 5



8. Exposure Controls and Personal Protection

Exposure Control Measures:	In the absence of data from National Occupational Health & Safety Commission (NOHSC) WorkSafe Australia use-: 1200mg/m³ TWA (8hr).		
Biological Monitoring:	No biological limit allocated.		
Engineering Controls:	Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapors. Keep containers closed when not in use.		
Individual Protection Measures:	Eye and face protection: Skin protection: Respiratory protection: Thermal Hazards:	Wear safety goggles. Use solvent resistant gloves, nitrile for longer term protection of PVC and neoprene for incidental splashes. If work practices do not maintain airborne levels below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapors (boiling point >65°C). respirators should comply with AS1716 or an equivalent approved by a state/territory authority. Not applicable.	

9. Physical and Chemical Properties

Appearance:	Amber Brown mobile Liquid	Density (g/ml@15ºC):	0.805 – 0.825
Odour:	Typical	Solubility (kg/m³):	Not miscible with water
Initial Boil point range:	250-330ºC	Auto ignition temp (ºC)	Typical 230
Flash Point:	115ºC	Vapour Density: (air=1@15ºC)	>1
Flammability:	Combustible	Upper/lower flammability: or explosive limits (%)	1.0 - 6.0
Vapour pressure: (kPa@20ºC)	Typical 0.001		

10. Stability And Reactivity

Reactivity:	Stable under normal conditions of use.		
Chemical Stability:	Stable under normal conditions of use.		
Possible Hazardous reactions:	Stable under normal conditions of use.		
Conditions to avoid:	Avoid heat, sparks, open flames, and other ignition sources.		
Incompatible materials:	Strong acids and strong oxidizing agents.		
Hazardous Decomposition products:	Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids, gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.		

CHASSIS SHIELD SDS Issued: October 10, 2025 Page 3 of 5



11. Toxicological Information

Acute toxicity:	Expected to be of low toxicity - LD50 Oral (rat) > 5000 mg/kg.		
Skin corrosion/irritation:	Prolonged contact may cause defatting of skin which can lead to dermatitis.		
Serious eye damage/irritation:	May cause irritation to eyes.		
Respiratory or skin sensitization:	Not expected to be a sensitizer.		
Germ cell mutagenicity:	Not expected to be mutagenic.		
Carcinogenicity:	Not expected to be carcinogenic		
Reproductive toxicity:	Not expected to impair reproduction.		
Specific Target Organ Toxicity (STOT) – single exposure	No data available.		
Specific Target Organ Toxicity (STOT) – repeated exposure	No data available.		
Aspiration hazard:	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.		

12. Ecological Information

Ecotoxicity - Acute toxicity:

Fish:	Low toxicity: LC/EC/IC50 <= 1000mg/I	
Aquatic invertebrate	Low toxicity: LC/EC/IC50 <= 1000mg/l	
Algae	Low toxicity: LC/EC/IC50 <= 1000mg/I	
Microorganisms	Data not available.	
Ecotoxicity – Chronic toxicity:		
Fish:	Data not available.	
Aquatic invertebrate	Data not available.	
Algae	Data not available.	
Microorganisms	Data not available.	

Persistence and degradability

Expected to be biodegradable. Degrades rapidly in air by photo-chemical means.

Bio accumulative potential

Data not available.

Mobility in soil

Floats on water. Adsorbs to soil and has low mobility.

13 Disposal Considerations

Disposal Considerations	Ensure waste disposal conforms to local waste disposal regulations.

CHASSIS SHIELD SDS Issued: October 10, 2025 Page 4 of 5



14. Transport Information		
UN number:	Not applicable	
Proper shipping name:	Not applicable	
Australian Dangerous Goods class:	Not applicable	
Australian Dangerous Goods packing group:	Not applicable	
Hazchem code:	Not applicable	

15. Regulatory Information		
Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP), Poisons Schedule:	5	
Australian Inventory of Chemical Substances (AICS)	Listed	
Dangerous Goods Initial Emergency Response Guide:	Not applicable	

16. Other Information

(SAA/SNZ HB76):

This SDS contains only safety related information. For other information see product literature.

Every endeavor has been made to ensure that the information contained in this publication is reliable and offered in good faith. It is meant to describe the safety requirements of our products and should not be construed as guaranteeing specific properties. Customers are encouraged to conduct their own tests as end user suitability of the product for uses is beyond our control. The information is not intended as an inducement to bargain and no warranty expressed or implied is made as to its accuracy, reliability, or completeness. Sierra Pty Ltd accepts no liability for loss, injury or damage arising from reliance upon the information contained in this data sheet except in conjunction with the proper use of the product to which it refers. Due care should be taken that the use and disposal of this product follows appropriate Federal, State and Local Government regulations.

CHASSIS SHIELD SDS Issued: October 10, 2025 Page 5 of 5